



Thermal-magnetic circuit-breakers GV7-R for connection by screw clamp terminals

Control by rocker lever

Standard power ratings of 3-phase motors 50/60 Hz in category AC-3									Setting range	Reference
400/415 V			500 V			660/690 V			of thermal	
P	Icu	Ics (1)	P	Icu	Ics (1)	P	Icu	Ics (1)	trips	
kW	kA		kW	kA		kW	kA		A	
7.5	25	100	9	18	100	11	8	100	12...20	GV7RE20
9	25	100	11	18	100	15	8	100		
7.5	70	100	9	50	100	11	10	100	12...20	GV7RS20
9	70	100	11	50	100	15	10	100		
9	25	100	11	18	100	15	8	100	15...25	GV7RE25
11	25	100	15	18	100	18.5	8	100		
9	70	100	11	50	100	15	10	100	15...25	GV7RS25
11	70	50	15	50	100	18.5	10	100		
18.5	25	100	18.5	18	100	22	8	100	25...40	GV7RE40
			22	18	100					
18.5	70	100	18.5	50	100	22	10	100	25...40	GV7RS40
22	25	100	30	18	100	30	8	100	30...50	GV7RE50
37	25	100	45	18	100	55	8	100	48...80	GV7RE80
			55	18	100					
37	70	100	45	50	100	55	10	100	48...80	GV7RS80
			55	50	100					
45	25	100	-	18	100	75	8	100	60...100	GV7RE100
45	70	100	-	50	100	75	10	100	60...100	GV7RS100
55	35	100	75	30	100	90	8	100	90...150	GV7RE150
75	70	100	90	30	100	110	8	100		
55	70	100	75	50	100	90	10	100	90...150	GV7RS150
75	70	100	90	50	100	110	10	100		
90	35	100	110	30	100	160	8	100	132...220	GV7RE220
110	35	100	132	30	100	200	8	100		
			160	30	100					
90	70	100	110	50	100	160	10	100	132...220	GV7RS220

(1) as % of Icu